

(19)  **Europäisches Patentamt**
European Patent Office
Office européen des brevets



(11) **EP 1 122 934 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
08.08.2001 Bulletin 2001/32

(51) Int Cl.7: **H04M 1/2745**

(21) Application number: **00128064.3**

(22) Date of filing: **21.12.2000**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Herzig, Hans Peter**
65232 Traunstein (DE)
• **Martschink, Volker**
65195 Wiesbaden (DE)

(30) Priority: **02.02.2000 US 496548**

(74) Representative: **Gibson, Sarah Jane et al**
Motorola GmbH
Law Dept. Intellectual Property Section,
Hagenauer Strasse 47
65203 Wiesbaden (DE)

(71) Applicant: **MOTOROLA, INC.**
Schaumburg, IL 60196 (US)

(54) **Communication device with dial function using optical character recognition, and method**

(57) A communication device (200), such as a cellular mobile phone or a cordless phone, has a dial unit (208) for communication with a base station. An input device for dialling a phone number which forwards a coded dial signal (215) to the dial unit (208) is implemented as an optical character recognition (OCR) scan-

ner (210) that reads phone numbers (202) from a printed or hand-written original (201). Optionally, especially for recognising hand-writing, the scanner (210) sends graphical representations of input data to the base station that obtains the code dial signals by an external processor.




FIG. 11

Description

Field of the Invention

[0001] The present invention generally relates to a communication device, and, more particularly, to a portable phone.

Background of the Invention

[0002] A communication device is often used in a network having a plurality of nodes. When a user wants to establish a communication between the device and a node, then the user usually manually inputs a node identifier through a keyboard of the device.

[0003] For example, the device is a portable phone operating in a public or private telephone network where the nodes are further phones (e.g., cellular phones or fixed network phones). The user establishes a communication by dialing a phone number.

[0004] However, typing a number into a keyboard by a human might cause misled phone calls. A physically challenged person might not be able to use the keyboard.

[0005] Phones having a dial function that is supported by voice recognition became recently available on the market. Apart from technical problems occurring in a noisy environment, some users hesitate from speaking a phone number into the phone, for example, because they fear to disclose the number in public.

[0006] JP 9307617 teaches a portable phone where the number is dialled by a bar-code scanner; requiring that numbers have to be available in a bar-code format. US Patent 5,966,669 teaches a portable phone that can be connected to an external bar-code/OCR reader. Further references for OCR readers are US Patent 4,408,344, US Patent 4,075,605, US Patent 5,574,804, European Patent Specification EP 0063243B1, and European Patent Application EP 0062777A2.

[0007] The present invention seeks to provide a communication device which mitigate or avoid these and other disadvantages and limitations of the prior art.

Brief Description of the Drawings

[0008]

- FIG. 1 illustrates a communication device with a built-in OCR reader according to the present invention;
- FIG. 2 illustrates the communication device of FIG. 1 with more detail as well as illustrates a phone network base station;
- FIG. 3 illustrates the communication device of FIG. 1 having the reader implemented by a line scanner;
- FIG. 4 illustrates the communication device of FIG. 1 having the reader implemented by an auto-

focus objective;

FIG. 5 illustrates the communication device of FIG. 1 having the reader implemented by a contact camera;

5 FIG. 6 illustrates the communication device of FIG. 5 with a transparent camera;

FIG. 7 illustrates the communication device of FIG. 1 having the reader implemented as a visiting card reader;

10 FIG. 8 illustrates the communication device of FIG. 1 with a confirmation interface;

FIG. 9 illustrates the communication device of FIG. 1 with a sensor that activates the reader;

15 FIG. 10 illustrates a simplified method flow chart diagram of a method according to the present invention; and

FIG. 11 illustrates a portable phone in an embodiment of the communication device.

20 Summary of the Invention

[0009] With reference to FIGS. 1-11, the present invention is summarised as a communication device (100, e.g., portable phone) having a dial unit (108) to establish communication via a communication channel (109), the communication device (100) characterised by a built-in optical character recognition (OCR) reader (110) to receive a dial identification (102, e.g., phone number, internet address) from an original (101). Optionally, the dial identification (102) is a name and the communication device (102) has a look-up table to allocate a phone number for that name. Preferably, the reader (110) comprises an optical scanner (120) and a character recognition processor (130, convenient with reduced recognition algorithm that recognises numbers); the character recognition processor (130) recognises the presence of phone or fax number indicators on the original (102). Preferably, the reader (110) comprises an optical scanner (120), a transmitter (151) to send a graphical representation (155) of the dial identification (102) to an external character recognition processor (140, e.g., located in a base station), and a receiver (152) of a code representation (145) of the dial identification from the external processor (140). Preferably, further information (e.g., short message in a cellular phone network) from the original (101) is scanned for transmission to a further communication device. Preferably, the reader (110) receives the dial identification by a line scanner (121) when the communication device (100) is moved over the original (101) in a first direction during a predetermined reading time; preferably the reader (110) touches the original (101) by a wheel (107) to obtain synchronisation information.

55 [0010] Optionally, the reader (110) collects image data of the dial identification (102) by being in a predetermined distance (D, autofocus objective) from the original (101) during a predetermined data collecting time (TC); the reader (110) can have a contact camera (123)

that receives the dial identification (102) when touching the original (101); the contact camera (123) can be implemented on an outer surface (105) of the communication device (100); the outer surface (105) can be opposite to a display (162); the contact camera (123) can have an active background light (125); the contact camera (123) can have a florescent background light (126) that is activated before receiving the dial identification (102) by exposing the communication device (100) to environment light; the contact camera (123) can be implemented by a translucent material; the translucent material can also be transparent.

[0011] Preferably, the communication device (100) has a recess (106) for temporarily inserting the original (101) wherein the reader (110) is implemented at the recess (106). Preferably, the communication device (100) of claim 1 has a confirmation interface (160) that receives a confirmation from the user; wherein the confirmation interface (160) returns the recognised dial identification (102) to the user; optionally the confirmation interface (160) returns the recognised dial identification to the user through a voice generator (161) and a loudspeaker (162); optionally the confirmation interface (160) returns the recognised dial identification (102) to the user with a display (163) that is visible to the user when the reader (110) is operating; optionally the confirmation interface (160) returns the recognised dial identification (102) to the user together with a redundant check information derived from the dial identification (102).

[0012] Preferably, the reader (110) is activated by a sensor (170) that senses the presence of the original (101); preferably, implemented by a mechanical switch (175).

[0013] Optionally, the communication device (100) has a loudspeaker (162) to output a representation of the dial identification (102) by a dual tone multi frequency (DTMF) signal.

[0014] A dial assistance device has a loudspeaker to dial a phone number by outputting a dual tone multi frequency (DTMF) signal characterised by a built-in optical character recognition (OCR) reader (110) to scan a printed representation of the phone number from paper and converting into the signal.

[0015] A method (300) for communicating a node identifier (102) through a portable communication device (100) to a network having a plurality of nodes, wherein the identifier (102) is available on an original (101), the method (300) comprises the steps of: scanning (310) at least partially the original (101) into a memory (135) of the communication device (100) to obtain a graphical representation (155) of the identifier (102); converting (320) the graphical representation into a code representation by using OCR techniques (i.e., transmitting the graphical representation to an external processor and processing by the external processor to the code representation); and dialling (330) the code representation to the network.

Detailed Description of a Preferred Embodiment

[0016] FIG. 1 illustrates a simplified diagram of communication device 100 (hereinafter "device 100") with built-in OCR reader 110 according to the present invention. Illustrated are device 100, original 101, dial identification 102, dial unit 108, communication channel 109, and OCR reader 110.

[0017] Preferably, device 100 is a portable phone, such as a cellular phone (analogue or digital, e.g., GSM, CDMA), a cordless phone (e.g., DECT). Device 100 can also be a two-way radio. Device 100 establishes communication via channel 109 (e.g., radio connection) to an above mentioned network node (e.g., base station) by dialling with dial unit 108. The term "dialling" that is often used in connection with phones is intended to include here also "selecting" that is often used in the field of two-way radios.

[0018] Device 100 is characterised by built-in optical character recognition (OCR) reader 110 to receive dial identification 102 from an original 101 (e.g., paper, computer display screen, or any other substrate). Reader 110 can comprise a charge-coupled device (CCD) or other means for reading.

[0019] Dial identification 102 can be any written identifier (by hand, typewriter, or printed). Preferably, dial identification 102 is phone number or a name of a person (or institution etc.) to be called. Device 100 can also be adapted for communication with a fax machine. For simplicity, the term "phone number" used herein is intended to refer also to fax numbers. However, this is not limited; identification 102 can also be an internet address (e.g., "http/www..."). When identification 102 is a name then device 100 conveniently uses a look-up table (not illustrated) to allocate a phone number for the name. In the example, used herein, dial identification 102 is given by the phone number "0611 ..." (area code for the German city of Wiesbaden); with the ellipsis standing for any further combination, but of course device 100 can read any other phone number.

[0020] In operation, device 100 reads identifier 102, performs any of the well-known OCR procedures, and uses a coded representation (e.g., ASCII-code, see FIG. 2) of identification 102 to dial.

[0021] FIG. 2 illustrates device 100 with more detail as well as illustrates phone network base station 141. Illustrated are device 100 (dashed frame), original 101 (below), reader 110, optical scanner 120, character recognition processor 130, external character recognition processor 140, code representation 145 ("ASCII"), base station 141, transmitter 151, receiver 152, and graphical representation 155 (e.g., "0611" as pixels).

[0022] Reader 110 of device 100 preferably comprises optical scanner 120 and character recognition processor 130. Examples for OCR-readers are given, for example, in US Patents 5,574,804; 4,408,344; and 4,075,605.

[0023] Optionally, processor 130 can be coupled to or

can comprise memory 135 for storing phone numbers (or other identification 102) that have been recognised. Preferably, character recognition processor 130 has a reduced recognition algorithm that recognises numbers and control characters (such as hyphens and a few symbols) only, but not letters.

[0024] In a convenient embodiment, processor 130 recognises the presence of phone number indicators 102 (and/or fax number indicators, see above) on original 101. Such indicators can be keywords (e.g., in English "PHONE", "phone", "CALL", "telephone"), phrases (e.g., "CALL 1-800", "Call me under"), or pictograms (e.g., for "phone" as illustrated; language or country code identifiers with flags, etc.).

[0025] Recognition is not limited to the Latin alphabet, languages that use non-Latin characters (e.g., Russian, Korean, Chinese, Japanese) can also be considered.

[0026] Pictograms are also useful. For example, scanning the symbol "information" (cf. illustrated in original 101 on the right) would connect the user to directory enquiries or any other operator assisted information service. Further modifications are also useful. For example, device 100 can be coupled to an information network that allows the user to scan in keywords and to get connected to an assistant. For example, if the user would read in the words "hotel" and "Wiesbaden" then a call to the Tourist Information Service Centre in Wiesbaden could be established.

[0027] It is convenient to have processor 130 being part of device 100, but not essential for the present invention. Additionally to scanner 120, reader 110 can optionally comprise transmitter 151 to send graphical representation 155 (of dial identification 102) to external character recognition processor 140 and receiver 152 (of code representation 145) of dial identification from external processor 140. Preferably, transmitter 151 and receiver 152 operate through channel 109. This optional external recognition can be activated, for example, when dial identification 102 is written by hand and built-in processor 130 does not recognise the hand-writing. Preferably, external processor 140 is located in base station 141 (e.g., of a cellular phone network). In such an implementation, the network provider can charge the user for recognition ("pay per scan"). Reader 110 of device 100 can also scan further information (e.g., a picture) from original 101 to be transmitted to a further device (e.g., a fax machine, printer) without OCR. When OCR is used, then device 100 can transmit further information as a short message in a cellular phone network (so called SMS). This optional feature is useful, for example, to transmit addresses from a visiting card ("calling card", "business card", details FIG. 7).

[0028] FIG. 3 illustrates device 100 having reader 110 implemented by line scanner 121. Illustrated are device 100, original 101, dial identification 102, reader 110 and line scanner 121 with wheel 107 (optional).

[0029] Reader 110 receives dial identification 102 by line scanner 121 when device 100 is moved over original

101 in a first direction during a predetermined reading time (e.g., a few milliseconds). For example, the user can sweep device 100 over a text showing a phone number. Optionally, reader 110 touches original 101 by wheel 107 to obtain synchronisation information.

[0030] FIG. 4 illustrates device 100 having reader 110 implemented by an autofocus objective 122 projecting the picture to a CCD-matrix or other type of image sensor. Illustrated are device 100, original 101, dial identification 102, and reader 110 with autofocus objective 122.

[0031] Reader 110 collects image data of dial identification 102 by being in a predetermined distance D (e.g., 2...300 milli meters) from original 101 during a predetermined data collecting time. In other words, the user holds device 100 near original 101 that is snap-shooting.

[0032] FIG. 5 illustrates device 100 having reader 110 implemented by contact camera 123 where distance D is substantially zero. Illustrated are device 100 having outer surface 105, original 101, dial identification 102, reader 110, contact camera 123 with active background light 125 or florescent background light 126, as well as display 162.

[0033] Reader 110 comprises contact camera 123 that receives dial identification 102 when touching original 101 during a predetermined data collecting time TC (short as in FIG. 4). Preferably, camera 123 has equal or larger dimensions than original 101. For example, for a printed 12-digit phone number (14 point letters) that is about 30 milli meters long and 3 milli meters high, camera 123 could have that dimensions.

[0034] Contact camera 123 can be provided, for example, by a CCD-matrix that has the same dimensions as identification 102. Camera 123 can also be implemented by a scanning array with row and columns of photo sensitive diodes as explained in above mentioned US Patent 4,408,344.

[0035] Device 100 preferably incorporates camera 123 on an outer surface 105, preferably on its backside, opposite to display 162 (cf. FIGS. 6 and 8). The user simply puts device 100 on the original. It is an advantage of the embodiment in FIG. 5 that it is not required to move device 100.

[0036] FIG. 5 also illustrates how the light to operate camera 123 is obtained. Contact camera 123 can have active background light 125 (e.g., located inside device 100, light emitting diodes LEDs); or contact camera 123 has florescent background light 126 (e.g., layer above camera 123) that is activated before receiving dial identification 102 by exposing device 100 to environment light. A further way to obtain the light is mentioned in connection with FIG. 6.

[0037] FIG. 6 illustrates the device of FIG. 5 with a transparent camera. Illustrated are device 100, original 101, dial identification 102, contact camera 123, and LCD display 162. Contact camera 123 is based on a translucent material (e.g., glass, or polymer) to let environment light reaching original 102. If the material is also

transparent, then the user has the advantage to see original 102 while operating reader 110. Further, the material that carries camera 123 can have a liquid crystal display LCD for a confirmation function (details FIG. 8).

[0038] FIG. 7 illustrate device 100 having reader 110 implemented as a visiting card reader. Illustrated are device 100, original 101 (e.g., card), recess 106, and reader 110 (dashed). The user temporarily inserts original 101 into recess 106 (or pushes it through).

[0039] FIG. 8 illustrates device 100 with confirmation interface 160. Illustrated are device 100, dial identification 102, reader 110, interface 160, voice generator 161, loudspeaker 162, and display 163.

[0040] Device 100 receives a confirmation from the user via interface 160, for example, when the user presses key 169 ("DIAL"). Preferably, the user can also input a rejection (by a key or otherwise).

[0041] Confirmation interface 160 returns the recognised dial identification 102 to the user, for example through voice generator 161 and loudspeaker 162 or through display 163. Preferably, display 163 is arranged such that display 163 is visible to the user when reader 110 is operating. In the above mentioned example, where original 101 shows identification "0611", loudspeaker 162 would speak "zero-six-one-one" and/or display 163 would indicate "0611".

[0042] Optionally, interface 160 returns the recognised dial identification 102 to the user together with a redundant check information derived from dial identification. To use the example again, loudspeaker 162 would output "zero-six-one-one Wiesbaden" and/or display 163 would indicate "0611 Wiesbaden".

[0043] When in case of an recognition error, device 100 outputs "0911 Nürnberg" so that the user can easily recognise the error.

[0044] Further modifications can be implemented without departing from the scope of the present invention. For example, device 100 could memorise (cf. memory 135 in FIG. 2) frequently used area codes. In case of an infrequent recognised number, device 100 could ask the user to verify ("You really want to call to Nürnberg?").

[0045] FIG. 9 illustrates device 100 with sensor 170 that activates reader 110. Illustrated are device 100, original 101, sensor 170 as mechanical switch 175.

[0046] Reader 110 is activated by sensor 170 that senses the presence of original 101. Sensor 170 can be implemented, for example, by a proximity sensor. In the example of FIG. 9, sensor 170 is implemented by mechanical switch 175.

[0047] Further modifications, to device 100 can be accomplished. For example, dial unit 108 (cf. FIG. 1) can be implemented by a loudspeaker (e.g., loudspeaker 162 in FIG. 8) to output a representation of dial identification 102 by a dual tone multi frequency (DTMF) signal. Without the need to type in a single digit into a conventional phone keyboard or to read a phone number from paper by his or her eyes, the user can set up a phone

call by simply scanning a phone number and holding device 100 to the microphone of a conventional phone (channel 109). Such a "dial assistant" is convenient for users that are physically challenged.

[0048] Various further possibilities can be obtained when reader 110 is a colour reader. To mention only a few advantages, the above mentioned recognition of national flags would be enhanced. For example, tricolours used in many European countries can be distinguished with higher accuracy.

[0049] FIG. 10 illustrates a simplified method flow chart diagram of method 300 according to the present invention. Method 300 for communicating node identifier 102 through portable communication device 100 to a network (represented by base station 141 in FIG. 2) having a plurality of nodes (wherein identifier/phone number 102 is available on original 101) comprises the steps of scanning 310, converting 320, and dialling 330. In scanning step 310, original 101 is at least partially scanned into a memory (like memory 135) of device 100 to obtain graphical representation 155 (e.g., pixel image) of identifier 102. In converting step 320, graphical representation 155 is converted into a code representation, wherein OCR techniques are used. In dialling step 330, the code representation is send to the network.

[0050] Optionally, converting step 320 can comprise the steps transmitting 321 the graphical representation to an external processor (cf. processor 141 in FIG. 2) and processing 322 the graphical representation by the external processor to the code representation.



[0051] FIG. 11 illustrates portable phone 200 in a preferred embodiment of communication device 100 according to the present invention. Preferably, portable phone 200 is a cellular mobile phone or a cordless phone (mentioned above). As illustrated, portable phone 200 has loudspeaker 291, microphone 292, display 262 (optional) and dial unit 208 for communication with a base station (e.g., station 141 in FIG. 2). For simplicity, unit 208 is symbolised only by an antenna. As in most phones, phone 200 has an input device for dialling a phone number which forwards a coded dial signal 215 to dial unit 208. According to the present invention, the input device is implemented as scanner 210 (details in FIGS. 1-10) with a character recognition function to convert a written dial identifier 202 (cf. 102, phone number) on paper 201 (cf. original 101) to coded dial signal 215. FIG. 11 indicates that the user sweeps phone 200 over paper 201 by the hand in arrow direction (reverse direction also possible).

[0052] Preferably, scanner 210 is limited to recognise numbers. Optionally, scanner 210 converts alphanumeric representations (e.g., names, internet addresses) of dial identifier 202 to phone numbers by using a look-up table (not illustrated). When required, for example, to recognise hand-writing, scanner 210 sends graphical representations of input data to the base station that obtains the code dial signals (cf. external processor 140 in FIG. 2).

[0053] While the invention has been described in terms of particular structures, devices and methods, those of skill in the art will understand based on the description herein that it is not limited merely to such examples and that the full scope of the invention is properly determined by the claims that follow.

Claims

1. Communication device (100) having a dial unit (108) to establish communication via a communication channel (109), said communication device (100) characterised by a built-in optical character recognition (OCR) reader (110) to receive a dial identification (102) from an original (101), said reader (110) having an optical scanner (120) and a character recognition processor (130). 15
2. The communication device (100) of claim 1, wherein said character recognition processor (130) has a reduced recognition algorithm that recognises numbers. 20
3. The communication device (100) of claim 1, wherein said character recognition processor (130) recognises the presence of phone number indicators or fax number indicators on said original (102). 25
4. The communication device (100) of claim 1, wherein said reader (110) further comprises a transmitter (151) to send a graphical representation (155) of said dial identification (102) to an external character recognition processor (140), and a receiver (152) of a code representation (145) of said dial identification from said external processor (140). 30 35
5. The communication device (100) of claim 1, wherein said reader (110) collects image data of said dial identification (102) by being in a predetermined distance (D) from said original (101) during a predetermined data collecting time (TC). 40
6. The communication device (100) of claim 1, wherein said reader (110) comprises a contact camera (123) that receives said dial identification (102) when touching said original (101) during a predetermined data collecting time (TC). 45
7. The communication device (100) of claim 6 wherein said contact camera (123) has a florescent background light (126) that is activated before receiving said dial identification (102) by exposing said communication device (100) to environment light. 50 55
8. The communication device (100) of claim 1 having a recess (106) for temporarily inserting said original (101) wherein said reader (110) is implemented at said recess (106).
9. The communication device (100) of claim 1 wherein said reader (110) is activated by a sensor (170) that senses the presence of said original (101).
10. Method (300) for communicating a node identifier (102) through a portable communication device (100) to a network having a plurality of nodes, wherein said identifier (102) is available on an original (101), said method (300) comprising the step of: scanning (310) at least partially said original (101) into a memory (135) of said communication device (100) to obtain a graphical representation (155) of said identifier (102); converting (320) said graphical representation into a code representation by using OCR techniques; and dialling (330) said code representation to said network.
11. A dial assistance device having a loudspeaker to dial a phone number by outputting a dual tone multi frequency (DTMF) signal characterised by a built-in optical character recognition (OCR) reader (110) to scan a printed representation of said phone number from paper and converting into said signal.






FIG. 3




FIG. 4




FIG. 6




FIG. 5




FIG. 7




FIG. 10




FIG. 8




FIG. 9





FIG. 11



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 122 934 A3**

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
14.05.2003 Bulletin 2003/20

(51) Int Cl.7: H04M 1/2745, H04M 1/2755

(43) Date of publication A2:
08.08.2001 Bulletin 2001/32

(21) Application number: 00128064.3

(22) Date of filing: 21.12.2000

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
Designated Extension States:
AL LT LV MK RO SI

• Martschink, Volker
65195 Wiesbaden (DE)

(30) Priority: 02.02.2000 US 496548

(71) Applicant: MOTOROLA, INC.
Schaumburg, IL 60196 (US)

(74) Representative: Gibson, Sarah Jane et al
Motorola
European Intellectual Property Section
Law Department
Midpoint
Alencon Link
Basingstoke, Hampshire RG21 7PL (GB)

(72) Inventors:
• Herzig, Hans Peter
65232 Traunstein (DE)

(54) **Communication device with dial function using optical character recognition, and method**

(57) A communication device (200), such as a cellular mobile phone or a cordless phone, has a dial unit (208) for communication with a base station. An input device for dialling a phone number which forwards a coded dial signal (215) to the dial unit (208) is implemented as an optical character recognition (OCR) scan-

ner (210) that reads phone numbers (202) from a printed or hand-written original (201). Optionally, especially for recognising hand-writing, the scanner (210) sends graphical representations of input data to the base station that obtains the code dial signals by an external processor.




FIG. 11



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 12 8064

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	WO 99 49640 A (SIEMENS AG ;MAGGIONI CHRISTOPH (DE)) 30 September 1999 (1999-09-30)	1,9	H04M1/2745 H04M1/2755
Y	* page 3, line 35 - page 6, line 11; figures 1-3 *	10	
Y	GB 2 282 906 A (DATAQUILL LTD) 19 April 1995 (1995-04-19)	10	
A	* page 2, line 33 - page 7, line 35; figures 1,5 *	1-4	
X	EP 0 354 703 A (CANON KK) 14 February 1990 (1990-02-14)	1,3,8,9	
A	* column 2, line 15 - line 43 * * column 4, line 25 - line 34; figure 2 * * column 16, line 30 - line 55; figure 22 * * column 17, line 41 - column 20, line 25; figures 24,25 *	2,10	
X	DE 197 36 809 A (HERZOG GUSTAV) 25 February 1999 (1999-02-25)	1	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
A	* page 2; figures 1,2 *	10	H04M G06K
X	US 4 975 948 A (ANDRESEN DENNIS R ET AL) 4 December 1990 (1990-12-04)	11	
A	* column 3, line 12 - line 28 * * column 3, line 60 - column 4, line 52; figure 1 *	1,3,9,10	
A	US 5 144 654 A (KELLEY JAMES T ET AL) 1 September 1992 (1992-09-01)	1,3,10	
	* column 11, line 44 - line 63; figures 1,3 *		
A	DE 196 29 546 A (SIEMENS AG) 12 February 1998 (1998-02-12)	4	
	* the whole document *		
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 21 March 2003	Examiner Ayala Perriello, M
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 (3.82 (P)4/01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 12 8064

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

21-03-2003

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
WO 9949640	A	30-09-1999	WO	9949640 A1	30-09-1999
			EP	0985307 A1	15-03-2000
GB 2282906	A	19-04-1995	AT	169753 T	15-08-1998
			AU	675357 B2	30-01-1997
			AU	7703394 A	04-05-1995
			CA	2173249 A1	20-04-1995
			CN	1133100 A ,B	09-10-1996
			DE	69412505 D1	17-09-1998
			DE	69412505 T2	08-04-1999
			DK	723687 T3	10-05-1999
			EP	0723687 A1	31-07-1996
			EP	0840248 A2	06-05-1998
			ES	2122328 T3	16-12-1998
			WO	9510818 A1	20-04-1995
			GB	2282907 A ,B	19-04-1995
			HK	149296 A	16-08-1996
			JP	9505419 T	27-05-1997
			NZ	329708 A	30-08-1999
			US	6058304 A	02-05-2000
EP 0354703	A	14-02-1990	JP	2042854 A	13-02-1990
			JP	2072752 A	13-03-1990
			JP	2805764 B2	30-09-1998
			JP	2158875 A	19-06-1990
			DE	68918534 D1	03-11-1994
			DE	68918534 T2	23-03-1995
DE 19736809	A	25-02-1999	EP	0354703 A2	14-02-1990
			DE	19736809 A1	25-02-1999
US 4975948	A	04-12-1990	NONE		
US 5144654	A	01-09-1992	NONE		
DE 19629546	A	12-02-1998	DE	19629546 A1	12-02-1998

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82